



# Porcelain Conditioner

## Safety Data Sheet

### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture  
Product name : Porcelain Conditioner

#### 1.2. Recommended use and restrictions on use

Use of the substance/mixture : For RX only

#### 1.3. Supplier

##### Manufacturer

Reliance Orthodontic Products, Inc. 1540 West Thorndale Ave.  
Itasca, IL 60143 USA  
630-773-4009, during normal business hours  
[www.relianceorthodontics.com](http://www.relianceorthodontics.com)

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC - 24-Hour Hazmat Emergency Communications Center  
Domestic: 1-800-424-9300 Outside the U.S.: 1-703-527-3887, collect calls accepted

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Flammable liquids Category 2	H225	Highly flammable liquid and vapor
Serious eye damage/eye irritation Category 2	H319	Causes serious eye irritation
Skin sensitization, Category 1	H317	May cause an allergic skin reaction
Specific target organ toxicity (single exposure) Category 3	H335	May cause respiratory irritation

Full text of H statements : see section 16

#### 2.2. GHS Label elements, including precautionary statements

##### GHS-US labeling

Hazard pictograms (GHS-US) :



Hazard statements (GHS-US) :

H225 - Highly flammable liquid and vapor  
H317 - May cause an allergic skin reaction  
H319 - Causes serious eye irritation  
H335 - May cause respiratory irritation

Precautionary statements (GHS-US) :

P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking  
P233 - Keep container tightly closed  
P240 - Ground/Bond container and receiving equipment  
P241 - Use explosion-proof ventilating equipment  
P242 - Use only non-sparking tools  
P243 - Take precautionary measures against static discharge  
P261 - Avoid breathing vapors  
P264 - Wash hands thoroughly after handling  
P271 - Use only outdoors or in a well-ventilated area  
P272 - Contaminated work clothing must not be allowed out of the workplace  
P280 - Wear eye protection, face protection, protective gloves  
P302+P352 - If on skin: Wash with plenty of Wash skin with soap and water  
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower  
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing  
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P312 - Call a POISON CENTER, Call a doctor if you feel unwell  
P321 - Specific treatment (see First aid measures on this label)  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention  
P337+P313 - If eye irritation persists: Get medical advice/attention  
P363 - Wash contaminated clothing before reuse  
P370+P378 - In case of fire: Use carbon dioxide (CO2), dry extinguishing powder, dry sand,

# Porcelain Conditioner

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

extinguishing powder to extinguish  
P403+P233 - Store in a well-ventilated place. Keep container tightly closed  
P403+P235 - Store in a well-ventilated place. Keep cool  
P405 - Store locked up  
P501 - Dispose in a safe manner in accordance with local/national regulations

### 2.3. Other hazards which do not result in classification

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	GHS-US classification
Acetone, ACS Grade	(CAS-No.) 67-64-1	30 - 50	Flam. Liq. 2, H225
Ethanol/Denatured 190 PROOF	(CAS-No.) 64-17-5	30 - 50	Flam. Liq. 2, H225 Eye Irrit. 2, H319
3-(Trimethoxysilyl)propyl-2-Methyl-2-Propenoic Acid	(CAS-No.) 2530-85-0	1 - 5	Skin Sens. 1B, H317

Full text of hazard classes and H-statements : see section 16

## SECTION 4: First-aid measures

### 4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
First-aid measures after skin contact	: Wash with water and soap. Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Specific treatment (see First aid measures on this label). Wash contaminated clothing before reuse.
First-aid measures after eye contact	: Rinse immediately with plenty of water for 15 minutes. Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists.
First-aid measures after ingestion	: Give milk to drink. Drink plenty of water. Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

### 4.2. Most important symptoms and effects (acute and delayed)

Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.
Symptoms/effects after inhalation	: May cause an allergic skin reaction. May cause respiratory irritation.

### 4.3. Immediate medical attention and special treatment, if necessary

No additional information available

## SECTION 5: Fire-fighting measures

### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Dry chemical powder. Carbon dioxide. Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

### 5.2. Specific hazards arising from the chemical

Fire hazard	: Combustible. Highly flammable liquid and vapor.
Explosion hazard	: May form flammable/explosive vapor-air mixture.

### 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

# Porcelain Conditioner

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking.

##### 6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

##### 6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Ventilate area.

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

#### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapors are flammable.

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. No open flames. No smoking. Use only non-sparking tools. Avoid breathing mist, vapors. Use only outdoors or in a well-ventilated area.

Handling temperature : 20 - 25 °C

Hygiene measures : Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

#### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/... equipment.

Storage conditions : Store in a dry place. Keep only in the original container in a cool, well ventilated place away from : Keep in fireproof place. Keep container tightly closed.

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

Storage temperature : 20 - 25 °C

Storage area : Store in a well-ventilated place. Store in a dry area. Store in a cool area.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

Acetone, ACS Grade	(67-64-1)	
ACGIH	ACGIH TWA (ppm)	550 ppm
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	2400 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
NIOSH	NIOSH REL (TWA) (ppm)	250 ppm

#### 3-(Trimethoxysilyl)propyl-2-Methyl-2-Propenoic Acid (2530-85-0)

Not applicable

#### Ethanol/Denatured 190 PROOF (64-17-5)

Not applicable

#### 8.2. Appropriate engineering controls

No additional information available

# Porcelain Conditioner

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 8.3. Individual protection measures/Personal protective equipment

#### Personal protective equipment:

Avoid all unnecessary exposure.

#### Hand protection:

Wear protective gloves

#### Eye protection:

Chemical goggles or safety glasses

#### Respiratory protection:

Wear appropriate mask

#### Other information:

Do not eat, drink or smoke during use.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear, colorless liquid.
Color	: Colorless
Odor	: Alcohol odour
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: > 56 °C
Flash point	: -18 °C
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Highly flammable liquid and vapor.
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: < 1
Solubility	: Miscible with water.
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

Highly flammable liquid and vapor. May form flammable/explosive vapor-air mixture.

### 10.3. Possibility of hazardous reactions

Not established.

# Porcelain Conditioner

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame.

### 10.5. Incompatible materials

Strong acids. Strong bases.

### 10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide. May release flammable gases.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

<b>Acetone, ACS Grade (67-64-1)</b>	
LD50 oral rat	5800 mg/kg
LD50 dermal rabbit	> 20000 mg/kg
LC50 inhalation rat (ppm)	> 16000 ppm/4h
ATE US (oral)	5800 mg/kg body weight

<b>3-(Trimethoxysilyl)propyl-2-Methyl-2-Propenoic Acid (2530-85-0)</b>	
LD50 oral rat	> 2000 mg/kg body weight (Rat; Literature study)
LD50 dermal rat	> 2000 mg/kg body weight (Rat; Literature study)

<b>Ethanol/Denatured 190 PROOF (64-17-5)</b>	
LD50 oral rat	7060 mg/kg
LD50 dermal rat	N/A
LD50 dermal rabbit	N/A
LC50 inhalation rat (ppm)	20000 ppm
ATE US (oral)	7060 mg/kg body weight

Skin corrosion/irritation : Not classified  
Serious eye damage/irritation : Causes serious eye irritation.  
Respiratory or skin sensitization : May cause an allergic skin reaction.  
Germ cell mutagenicity : Not classified  
Carcinogenicity : Not classified

<b>Acetone, ACS Grade (67-64-1)</b>	
IARC group	4 - Probably not carcinogenic to humans

<b>Ethanol/Denatured 190 PROOF (64-17-5)</b>	
IARC group	4 - Probably not carcinogenic to humans

Reproductive toxicity : Not classified  
Specific target organ toxicity – single exposure : May cause respiratory irritation.

<b>Acetone, ACS Grade (67-64-1)</b>	
LOAEL (oral,rat)	N/A mg/kg body weight
LOAEL (dermal,rat/rabbit)	N/A mg/kg body weight
LOAEC (inhalation,rat,gas)	N/A ppmV/4h
LOAEC (inhalation,rat,vapour )	N/A mg/l/4h
LOAEC (inhalation,rat,dust/mist/fume)	N/A mg/l/4h

<b>Ethanol/Denatured 190 PROOF (64-17-5)</b>	
LOAEL (oral,rat)	N/A mg/kg body weight
LOAEL (dermal,rat/rabbit)	N/A mg/kg body weight
LOAEC (inhalation,rat,gas)	N/A ppmV/4h
LOAEC (inhalation,rat,vapour )	N/A mg/l/4h
LOAEC (inhalation,rat,dust/mist/fume)	N/A mg/l/4h

Specific target organ toxicity – repeated exposure : Not classified

<b>Acetone, ACS Grade (67-64-1)</b>	
LOAEL (oral,rat,90 days)	N/A mg/kg bodyweight/day

# Porcelain Conditioner

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>Acetone, ACS Grade (67-64-1)</b>	
LOAEL (dermal,rat/rabbit,90 days)	N/A mg/kg bodyweight/day
LOAEC (inhalation,rat,gas,90 days)	N/A ppmV/6h/day
LOAEC (inhalation,rat,vapour,90 days)	N/A mg/l/6h/day
LOAEC (inhalation,rat,dust/mist/fume,90 days)	N/A mg/l/6h/day

<b>Ethanol/Denatured 190 PROOF (64-17-5)</b>	
LOAEL (oral,rat,90 days)	N/A mg/kg bodyweight/day
LOAEL (dermal,rat/rabbit,90 days)	N/A mg/kg bodyweight/day
LOAEC (inhalation,rat,gas,90 days)	N/A ppmV/6h/day
LOAEC (inhalation,rat,vapour,90 days)	N/A mg/l/6h/day
LOAEC (inhalation,rat,dust/mist/fume,90 days)	N/A mg/l/6h/day

Aspiration hazard : Not classified

Potential Adverse human health effects and symptoms : Based on available data, the classification criteria are not met.

Symptoms/effects after inhalation : May cause an allergic skin reaction. May cause respiratory irritation.

## SECTION 12: Ecological information

### 12.1. Toxicity

<b>Acetone, ACS Grade (67-64-1)</b>	
LC50 fish 1	4740 - 6330 mg/l
LC50 fish 2	8300 mg/l

<b>3-(Trimethoxysilyl)propyl-2-Methyl-2-Propenoic Acid (2530-85-0)</b>	
LC50 fish 1	175 mg/l (LC50; 96 h)
EC50 Daphnia 1	> 100 mg/l (EC50; EU Method C.2; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)
LC50 fish 2	> 100 mg/l (LC50; EU Method C.1; 96 h; Brachydanio rerio; Semi-static system; Fresh water; Experimental value)
EC50 Daphnia 2	>= 100 mg/l (NOEC; EU Method C.2; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)
Threshold limit algae 1	> 100 mg/l (EC50; EU Method C.3; 72 h; Scenedesmus subspicatus; Static system; Fresh water; Experimental value)
Threshold limit algae 2	> 100 mg/l (EC50; EU Method C.3; 72 h; Scenedesmus subspicatus; Static system; Fresh water; Experimental value)

<b>Ethanol/Denatured 190 PROOF (64-17-5)</b>	
LC50 fish 1	14000 mg/l

### 12.2. Persistence and degradability

<b>Porcelain Primer</b>	
Persistence and degradability	Not established.

<b>3-(Trimethoxysilyl)propyl-2-Methyl-2-Propenoic Acid (2530-85-0)</b>	
Persistence and degradability	Readily biodegradable in water.

### 12.3. Bioaccumulative potential

<b>Porcelain Primer</b>	
Bioaccumulative potential	Not established.

<b>3-(Trimethoxysilyl)propyl-2-Methyl-2-Propenoic Acid (2530-85-0)</b>	
Log Pow	0.75 (Calculated)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

Effect on the global warming : No known effects from this product.

GWPmix comment : No known effects from this product.

Other information : Avoid release to the environment.

# Porcelain Conditioner

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 13: Disposal considerations

#### 13.1. Disposal methods

- Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose in a safe manner in accordance with local/national regulations.
- Additional information : Handle empty containers with care because residual vapors are flammable.
- Ecology - waste materials : Avoid release to the environment.

### SECTION 14: Transport information

#### Department of Transportation (DOT)

In accordance with DOT

- Transport document description : UN1170 Ethyl alcohol solutions, 3, III
- UN-No.(DOT) : UN1170
- Proper Shipping Name (DOT) : Ethyl alcohol solutions
- Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
- Packing group (DOT) : III - Minor Danger
- Hazard labels (DOT) : 3 - Flammable liquid



- DOT Packaging Non Bulk (49 CFR 173.xxx) : 203
- DOT Packaging Bulk (49 CFR 173.xxx) : 242
- DOT Special Provisions (49 CFR 172.102) : 24 - Alcoholic beverages containing more than 70 percent alcohol by volume must be transported as materials in Packing Group II. Alcoholic beverages containing more than 24 percent but not more than 70 percent alcohol by volume must be transported as materials in Packing Group III.  
B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable.  
IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).  
T2 - 1.5 178.274(d)(2) Normal..... 178.275(d)(3)  
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling =  $97 / 1 + a (tr - tf)$  Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
- DOT Packaging Exceptions (49 CFR 173.xxx) : 4b;150
- DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 60 L
- DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 220 L
- DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
- Emergency Response Guide (ERG) Number : 127
- Other information : No supplementary information available.

#### TDG

#### Transport by sea

Not regulated

#### Air transport

Not regulated

# Porcelain Conditioner

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

No additional information available

#### 15.2. International regulations

##### CANADA

No additional information available

##### EU-Regulations

No additional information available

##### National regulations

No additional information available

#### 15.3. US State regulations

No additional information available

### SECTION 16: Other information

Full text of H-phrases:

H225	Highly flammable liquid and vapor
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H335	May cause respiratory irritation

SDS US (GHS HazCom 2012)

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*